



TECHNICAL INFORMATION / TEKNISK INFORMATION



TOP TILE Antique Chestnut
AC1062




TOP TILE Cube
CU1062



TOP TILE Scratch
SC1062














TOP TILE Wood Nature
WO1062



TOP TILE Black Prism
PR1062

BERGO TOP TILE

For indoor use

Material:		ISO2076	Environmentally friendly recyclable UV- stabilized PP-composite. / Miljövämlig återvinningsbar UV-stabiliserad PP-komposit.
Size of tile: /Plattans storlek:		EN427	378 x 378 mm. 5 m ² / box = 35 tiles.
Thickness of tile: /Plattans tjocklek:		EN428	10,7 mm.
Weight: /Vikt:		EN430	1 tile: 0,750 kg. 1 m ² : 5,25 kg. 2 m ² = 10,7 kg (2 m ² -pack) 5 m ² : 26,25 kg (Maxi-pack).
Point load: /Punktbelastning:		QUALIFIED TEST BY BERGO	300 ton / 1 m ² = 3000 kg/dm ²
Light fastness: /Ljusbeständighet:		ISO 105-B02 (1-8)	7
Slip resistance: /Halkmotstånd:		SSEN-13893	>0,4
Impact resistance: /Slagtållighet:		ISO179/1eA ASTM D746	+23 °C = 20 kJ/m ² / -20 °C = 5 kJ/m ² C15 kJ/m ²
Chair castor /gaffelhjul möbler och kontorstolar.		SS-EN 12529	Continuous use
Fire category /Brandklassning:		EN ISO 9239-1	C _{fl}
CE certification:		EN 14041	0402-CPD-P605080A

Packaging:	Quantity / packaging unit:	Quantity / pallet:	Size of pallet:
2m ² -pack	2 m ² = 14 tiles = 10,7 kg	1 pallet = 42 cartons = 84 m ²	1,2 x 0,80 x 1,18 m = 1,2 m ³ = 1,2 m ³
Maxi-pack	5 m ² = 35 tiles = 25,8 kg	1 pallet = 18 cartons = 90 m ²	1,20 x 0,80 x 1,20 m = 1,16 m ³ , 480 kg gross weight



By normal use and treatment
the material guarantee time
is 10 years.



Bergo Flooring AB fulfills the
requirements of ISO 9001.



Bergo Floors are
100% recyclable.



SYSTEM
2

Patent.

www.bergoflooring.com

